

Keypoints:

- Conform Intel ATX 12v ver 2.0 and EPS 12v
- Active PFC (Power factor correction)
- Cable length at least 45 cm
- Silent 14cm fan (automatic speed control)
- Modular cable design
- OCP / OVP / SCP Protections



Specifications:

Description	
Article number	RC-PEM600
Packaging unit (per carton)	6 Pieces
Net weight per piece	2,23 Kg
Gross weight per piece	2,85 Kg
Gross weight per carton	18,0 Kg
Net dimensions per piece (W x H x D)	16 x 15 x 8,6cm
Gross dimensions per piece (W x H x D)	24 x 10 x 22cm
Gross dimensions per carton (W x H x D)	32 x 26 x 45 cm
Color	Black coated shell
On-Off power switch	Yes
Accessories	2 Pcs. Cable ties 4 Pcs. Black screws AC Powercable (CE)

Connectors:

Description	
M/B 20+4Pins	1 Pc.
M/B 4+4 Pins ATX	1 Pc.
Pci-E 6+2 Pins	1 Pc.
Pci-E 6 Pins	1 Pc.
SATA 15 Pins	6 Pcs.
MOLEX 4 Pins	4 Pcs.
FDD 4 Pins	1 Pc.

Delivered cables:

	Connection	Connector 1	Connector 2	Connector 3	Amount
Mainboard atx	Onboard	45cm 20+4 Pins			1 Cable
Mainboard 12v	Onboard	45cm 4+4 Pins			1 Cable
Graphics	Onboard	45cm 6 Pins			1 Cable
Graphics	Onboard	45cm 6+2 Pins			
Peripherals	Modular	40cm SATA 15 Pins	+15cm SATA 15 Pins		2 Cables
Peripherals	Modular	40cm Molex 4Pins	+15cm Molex 4 Pins		1 Cable
Peripherals	Modular	40cm Molex 4Pins	+15cm Molex 4 Pins	+15cm FDD 4Pins	1 Cable

Technical Specifications:

MODEL								
Recom RC-PE-M600								
AC INPUT								
230VAC, 6A, 50hz								
DC OUTPUT								
	+3.3V	+5V	+12V1	+12V2	+12V3	+12V4	-12V	+5VSB
Max Amps	25A	25A	22A	22A	n/a	n/a	0,5A	2A
Max Combined	160W		432W			6W		10W
Total Combined	584W						16W	
Total power	600W							

